

# PERFO-EQ

## Stepped Tile

### Technical Specifications

|  |   |
|--|---|
| Material:                                    | PE / PP   |
| Colour:                                      | Black   |
| Closed surface area (load bearing):          | 50% + 50%, in two tiers   |
| Surface structure:                           | raised points for grip / drainage channels  |
| Load bearing capability:                     | approx. 100 tonnes/m <sup>2</sup> *<br>* depending on ground conditions and preparation |
| Dimensions (individual tile)**               | 300 x 300 x 35 mm   |
| **not including connecting lugs              |   |
| Weight per tile:                             | 470 g   |
| Dimensions as supplied<br>(made-up section): | 121 x 91 cm<br>4 x 3 Perfo-EQ tiles   |
| Area per made-up section:                    | approx. 1.1 m <sup>2</sup>  |
| Weight per made-up section:                  | approx. 6.2 kg  |
| No. of sections per pallet:                  | 55  |
| Total surface area per pallet:               | approx. 60 m <sup>2</sup>   |
| Weight per pallet:                           | approx. 330 kg  |
| Height per pallet:                           | approx. 220 cm  |

Resistant to oil, solvents, salt water,  
most acids.

UV and frost resistant

Does not rot

Non-perforated white tiles for marking purposes,  
eg. to demarcate parking bays or for centre-lines  
are also available on request.

